

GEO-SYSTEMS USA

GENUINE EXCELLENCE. INFINITE POSSIBILITIES.

Geo Loop Leak Seal & Conditioner Instructions

SHAKE WELL BEFORE USING

CAUTION: Not to be used in systems with strainers or transducers unless they can be isolated from the product.

For preventative maintenance of vertical or horizontal ground loops, mix one 8 oz. bottle and add to geothermal loop field while purging the system, or by introducing through P/T port if the system is up and running , or through the water storage tank in an atmospheric flow center situation where reflushing is not necessary.

Add 8 oz. of Geo-Loop Leak Seal and Conditioner for each five tons of ground loop. If you expect the loss of water as the result of a bad fusion, add double the amount of Geo-Loop Leak Seal and Conditioner suggested above.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. CAUSES SEVERE EYE AND SKIN IRRITATION. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. HARMFUL OR FATAL IF SWALLOWED. AVOID CONTAMINATION OF FOOD. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER AND DISCARD.

Geo-Systems USA does not assume any responsibility for the performance of this product.

1-866-522-0396

972-522-0396

www.geosystemsusa.com