

POCKET TEST THERMOMETER

Bimetal Type - 1" Dial - 5" Stem

Miljoco Pocket Test Thermometers are ideal for use as test instruments in the HVAC, plumbing, refrigeration, and appliance repair industries. These thermometers are furnished with a durable plastic carrying case and pocket clip. They are also available with either a domed or magnifying lens and can be recalibrated easily in the field. Various ranges are NSF® listed for use in the food service industry.

General Specifications

CASE: Hermetically sealed 300 series stainless steel.

LENS: Acrylic.

DIAL: Aluminum, white finished with black markings.

POINTER: Red.

RECALIBRATOR: External adjusting hex nut or recalibrator lug on rear of case.

STEM: 300 series stainless steel, Ø 0.150".

ACCURACY: ±2% full range.

AMBIENT TEMPERATURE: -40 to 140°F (-40 to 60°C).



Models

Model	Range	Dial Size	Stem Length	Lens Type	Adjustment Type
B1098M90C-5.0	-40 to 160°F	1"	5"	Magnifying	Recalibrator Lug
B1098M82C-5.0	0 to 220°F*	1"	5"	Magnifying	Recalibrator Lug
B1098M43C-5.0	25 to 125°F*	1"	5"	Magnifying	Recalibrator Lug
B1098M95C-5.0	50 to 500°F	1"	5"	Magnifying	Recalibrator Lug
B1098M28C-5.0	0 to 100°C	1"	5"	Magnifying	Recalibrator Lug
B1098M42C-5.0	-40 to 70°C	1"	5"	Magnifying	Recalibrator Lug
B1098D90A-5.0	-40 to 160°F	1"	5"	Domed	Hex Nut
B1098D82A-5.0	0 to 220°F*	1"	5"	Domed	Hex Nut
B1098D43A-5.0	25 to 125°F*	1"	5"	Domed	Hex Nut
B1098D95A-5.0	50 to 500°F	1"	5"	Domed	Hex Nut
B1098D28A-5.0	0 to 100°C	1"	5"	Domed	Hex Nut
B1098D42A-5.0	-40 to 70°C	1"	5"	Domed	Hex Nut

*NSF® listed range.

